

3773 STATE ROAD CUYAHOGA FALLS, OH 44223

MODEL " i " 971 PVC CASEMENT WINDOW "NON-IMPACT"

ALSO DISTRIBUTED UNDER THE FOLLOWING TRADE NAMES:


ASSOCIATED MATERIALS, INC.
GENTEK BUILDING PRODUCTS
REVERE BUILDING PRODUCTS

EVALUATED FOR USE IN THE STATE OF TEXAS


The Casement Window described herein complies with the 2006 International Residential Code (IRC), Sections R301 & R613 and the 2006 International Building Code (IBC), Sections 1405.12, 1609, 1714.5, 2403 and 2404 (including Texas revisions) subject to the following conditions:

- 1. Anchors shall be as listed and spaced as shown in the details. Anchor embedment to base material shall be beyond wall dressing or stucco.
- 2. When used in areas requiring wind-borne debris protection this product is required to be protected with an impact resistant covering that complies with Section R301.2.1.2 of the IRC and Section 1609.1.2 of the IBC.
- 3. Allowable design pressure requirements must be equal to or less than the design pressure rating shown in the design pressure chart, sheet 1 of this drawing.
- 4. Conditions not covered by this drawing are subject to further engineering analysis.

	TABLE OF CONTENTS
SHEET#	DESCRIPTION
1	Typical elevations, design pressures & general notes
2	Frame anchoring & cross sections
3	Bill of materials, glazing details and components



7	Documents Prepared By:			BUILDING CONS	JC P.O. Box 230	LION PHONE OF	TEXAS BOARD OF PROFE	CERTIFICATE OF REGISTI	
	PRODUCT:	FIXED WINDOW			PART OR ASSEMBLY:	אסוסקט ואסודאים ויי ואסומאד	DESCRIBES & CENTERAL MOTES	FACSSORES & GENERAL NOTES	
							ВУ		
							NO. DATE	REVISIONS	© 2013 R.W. BUILDING CONSULTANTS INC.
	DA [*]	TE: ALE	_	_	27. I.T.	_	_		LDIN
	DW	G.	BY:		ì	JK			· Bu
			BY:	NO		FS	5		R.W
						12	S.		2013
	SH	EET	-	1	OF	_	3_		0



ects\Project Folders\proj 1401-1500\PF 1441\D. RWBC Draw

BILL OF MATERIALS				
ITEM #	DESCRIPTION	MATERIAL		
В	2X FRAMING (SG >= 0.42)	WOOD		
С	1/4" MAX. SHIM SPACE	-		
F	#8 X 2-1/2" PFH SMS	STEEL		
1	EXTRUDED VINYL SASH FRAME *	RIGID PVC		
2	EXTRUDED VINYL GLAZING BEAD *	RIGID PVC		
3	EXTRUDED VINYL MAIN FRAME *	RIGID PVC		
4	HOT MELT BUTYL	SILICONE		
5	SASH REINFORCEMENT (3205)	STEEL		
6	STEEL INTERCEPT SPACER	STEEL		
7	LOCK HANDLE w/ GASKET (TRUTH)	22		
8	TIE BAR (TRUTH) & GUIDE w/ #8 x 1" PPH SMS	STEEL		
9	OPERATOR HANDLE (TRUTH)			
10	SNUBBER (ASHLAND) w/ #8 x 1/2" PPH SMS	STEEL		
11	KEEPER	-		

^{*} THE APPROVED WHITE RIGID PVC EXTERIOR EXTRUSIONS FOR WINDOWS ARE TO BE PRODUCED BY EXTRUDERS LICENSEES IN "AAMA CERTIFICATION PROGRAMS FOR RIGID PVC EXTRUSIONS".

